

ALUMICLAD®

STANDARD COLOURS



White
YLE01



Ivory White
YLE02



Off White
YLE03




Grey
YLE04



Silver Metallic
YLE05



Silver Grey
YLE06



Champagne Metallic
YLE07



Golden Metallic
YLE08



Yellow
YLE09



Green
YLE010



Moss Green
YLE011



Sky Blue
YLE012



Red
YLE013



Ocean Blue
YLE014




Navy Blue
YLE015



Sea Green
YLE016

General Information

Alumiclad® is available in Alumiclad®10 or Alumiclad®15. Alumiclad®10 is a durable and weather resistant coating best suited for internal and low level façade applications not in proximity to the coastline. Alumiclad®15 is a PVDF coating, which is extremely resistant against weathering, UV rays and harmful pollutants and is recommended for exterior use and premium architectural applications. These coatings are applied to the aluminium coil prior to lamination into a composite panel, using a continuous coil coating and baking process, which is based on the latest technology. These consistent and quality coatings in a range of colours will aesthetically enhance any building as well as protect it from the elements. Colours not listed in this chart are available on request and subject to minimum order quantities. Colour reproduction in this chart is subject to printing limitations. For consistency of colour, batches should not be mixed. Please refer to additional technical advice for storage, installation and cleaning of panels. All products supplied and technical advice provided are subject to the standard terms and conditions of sale of Alumiclad® products.



ALUMICLAD®

STANDARD COLOURS



Mist Green Metallic
YLE017



Champagne Gold Metallic
YLE018



Cream
YLE019



Aluminum
YLE020



Black
YLE021



Bronze
YLE022



Peacock Green
YLE023



Turquoise
YLE024



Ruby
YLE025



Orange
YLE026



Bluestone
YLE030



Bronze Metallic
YLE031



Charcoal Pearl
YLE032



Titanium
YLE033



Ironstone
YLE034



Light Grey Pearl
YLE035

General Information

Alumiclad® is available in Alumiclad® 10 or Alumiclad® 15. Alumiclad® 10 is a durable and weather resistant coating best suited for internal and low level façade applications not in proximity to the coastline. Alumiclad® 15 is a PVDF coating, which is extremely resistant against weathering, UV rays and harmful pollutants and is recommended for exterior use and premium architectural applications. These coatings are applied to the aluminium coil prior to lamination into a composite panel, using a continuous coil coating and baking process, which is based on the latest technology. These consistent and quality coatings in a range of colours will aesthetically enhance any building as well as protect it from the elements. Colours not listed in this chart are available on request and subject to minimum order quantities. Colour reproduction in this chart is subject to printing limitations. For consistency of colour, batches should not be mixed. Please refer to additional technical advice for storage, installation and cleaning of panels. All products supplied and technical advice provided are subject to the standard terms and conditions of sale of Alumiclad® products.

